

RL2000 - Woodpecker HV Cable Identifier

Data Sheet

- High Voltage Dead Cable Identifier
- Identify HV cables from LV cables
- Order code: 64598754



Receiver

Operating Frequency	625Hz
Audio Indication	Internal Loudspeaker
Visual Indication	Analogue meter showing signal strength
Battery State	LED battery level indication
Search Antenna	High gain search coil
Filter	Switched capacitor type
Gain Control	Manual Rotary 120dB (max)
Batteries	1x 9V PP3/6LR61 40 hrs life (approx)
Operating temp range	-15°C to +50°C
Weight (shipping)	2.2Kgs (receiver and transmitter combined)

Transmitter

Operating Frequency	625Hz
Battery State	Red Green LED
Locate Range	Up to 15km
Signal	Constant or pulsed sine wave
Output protection	Transformer isolate
Batteries	6x 1.5V LR14 'C' cells, 40 hrs life (approx)
Operating temp range	-15°C to +50°C
Output protection	Matching transformer isolated



Leaders in Utility Instrumentation

Bicotest Ltd,
Hellesdon Park Road,
Drayton High Road,
Norwich,
UK, NR6 5DR

Tel + 44 (0) 1603 416 900
Fax + 44 (0) 1603 416 902
enquiries@bicotest.co.uk
www.bicotest.co.uk